

Decorated Standard Particleboard

Technical Data Sheet


Formica[®] Decorated STD E1 Particleboard is a particleboard bonded on both sides with a hardwearing melamine decorative surface suitable for dry area applications.

APPLICATIONS

- Wardrobes
- · Cabinetry

- Cabinetry Doors & Drawers
 Shelving
 Wall Panels
- Cabinetry Interiors & Panels

FUNCTIONAL BENEFITS



Product Characteristics

ATTRIBUTE	DESCRIPTION	
Product Category	Low Pressure Melamine	
Substrate Type	Standard E1 Particleboard	
Sheet Size (nominal)	2400mm x 1200mm, 3600mm x 1200mm	
Thickness (nominal)	16mm	
Weight (Kg/m2 approx.)	10.2	
Finish	Velvet, Pearl and Grain	
Colour/Pattern	To view the full range, please visit www.formica.com.au	

Laminex reserves the right to update this document prior to the stated expiry date. Refer to www.formica.com.au for the latest revision of this document.

Technical Data Sheet

Dimensional Tolerance

(Tested to AS/NZS 4266.1)

ATTRIBUTE	MEASUREMENT
Thickness ±0.6mm	
Length and Width	+5mm / -5mm maximum deviation
Squareness	2mm/m maximum deviation
Flatness	1.5mm/m maximum deviation (measured in horizontal)

Surface Quality (Tested to AS/NZS 4266.2)

ATTRIBUTE	MEASUREMENT
Inspection Guidelines	Viewing distance 1.5m from decorative surface Light intensity approximately 800 to 1000 lx at the decorative surface Using normal vision, corrected if necessary. No magnification devices
Dirt, Spots & Similar Surface Defects	The admissible size of defects is based on a maximum contamination area equivalent to 1.0mm ² /m ² and is proportional to the sheet size under inspection
	The total admissible area of contamination may be concentrated in one spot or dispersed over an unlimited amount of smaller defects
Fibres, Hairs & Scratches	The admissible size of defects is based on a maximum contamination length equivalent to 10mm/m ² and is proportional to the sheet size under inspection
	The total admissible length of contamination may be concentrated in one defect or dispersed over an unlimited amount of smaller defects

Technical Data Sheet

Surface Performance (Tested to AS/NZS 4266.2)

ATTRIBUTE	MEASUREMENT
Resistance to Surface Abrasion	Printed patterns ≥ 40 cycles. Solid colours ≥ 300 cycles
Resistance to Scratching	Velvet finish ≥ 2 Newton. Pearl & Grain finishes ≥ 4 Newton
Porosity	Appearance rating not worse than 3
Resistance to Steam	Appearance rating not worse than 3 Moderate swelling
Resistance to Cracking	No visible cracks or micro cracks
Resistance to Staining	Rating ≤ 2 Faint stain left on surface
Lightfastness ISO 4586-2	Contrast: Grey scale rating \geq 4 When tested in contrast with Blue wool 6 Ref: ISO 105-A02
Colour Variation ISO 105-A05	Surface material "batch to batch" colour variation of $\triangle E \leq 1$

Surface Adhesion Performance

(Tested to AS/NZS 4266.2)

ATTRIBUTE	MEASUREMENT
Bond Strength	≥ 1.3 MPa

Technical Data Sheet

Substrate Performance (Tested to AS/NZS 4266.1)

			MEASUREMENT	SUREMENT	
ATTRIBUTE	UNITS	MINIMUM VALUES	TYPICAL VALUES#		
Density	Kg/m ³	-	640 ± 30		
Internal bond	MPa	0.30	0.45 – 0.60		
Modulus of Rupture	MPa	12	13 – 15		
Modulus of Elasticity	MPa	1600	2300 - 2700		
Surface Soundness	MPa	0.9	1.1 - 1.3		
Screw Holding, Face	Force N	1000	1000 - 1200		
Screw Holding, Edge	Force N	600	600 - 700		
Thickness Swell (24hr)	%	-	17.0 – 22.5		
Formaldehyde	mg/L	≤ 1.5	E1 ≤ 1.5		

#Table contains representative values only. Performance variation outside stated typical values does not constitute a product failure.

Specialty Performance

ATTRIBUTE	TESTED TO:	TYPICAL VALUES		
Fire Hazard Properties	AS/NZS 3837 (In accordance to AS5637.1)	Group Number	3	
		Average Specific Extinction Area (ASEA)	19.8 m²/Kg	

Emissions & Environmental Performance

ATTRIBUTE	TESTED TO	UNITS	MEASUREMENT
Formaldehyde	AS/NZS 1859.1	mg/L	E1 ≤ 1.5
Volatile Organic Compounds (VOC's)	ASTM D5116	mg/m²/h	≤ 0.5

Technical Data Sheet

Important Information

NOTE		DETAILS		
W	ONLY use for internal applications	Claims arising from non-internal applications are not covered under warranty		
W	ONLY use for dry area applications	Claims arising from wet ar	ea applications are not covered und	er warranty
W	CAUTION! - Darker colours will show fingerprints, scratches and superficial wear & tear more readily than lighter colours	Claims arising from fingerprints, scratches or superficial wear & tear directly attributable to the selection of a dark colour, are not covered under warranty		
W	DO NOT expose to prolonged direct or indirect UV light			artificial sources) resulting in shrinkage and/ ent, are not protected under warranty
W	Use of different surface materials within a single installation may result in a perceived visual variation	Claims arising from colour, gloss or finish variation between different product groups, including products with different UV or aging stabilities, are not covered under warranty		
W	Use of directional designs or finishes in opposing orientations may result in a perceived visual variation	Claims arising from colour covered under warranty	gloss or finish variation directly attr	ibutable to surface directionality, are not be
W	ALL material must be inspected prior to commencing any fabrication activity	Claims arising from defects or variation clearly detectable prior to fabrication, will not be covered under warranty for labour costs or penalties		
W	ONLY use recommended hinge quantities	je quantities Claims arising from bow, warp or twisting due to too few hinges or inappropriate door sizes or v are not covered under warranty		es or inappropriate door sizes or weights,
		Door Height (mm)	Door Weight (Kg)	No. of Hinges
		≤ 900 mm	≤ 9 Kg	2
		≤ 1600 mm	≤ 15 Kg	3
		≤ 2000 mm	≤ 19 Kg	4
		≤ 2400 mm	≤ 23 Kg	5
W	DO NOT use large door dimensions	Claims arising from bow, warp or twisting of doors greater than 600mm wide, are not covered under warranty		
W	DO NOT leave edges unsealed	Claims arising from the effect of heat or moisture ingress attributable to exposed edges of panels, are not covered under warranty		
W	DO NOT apply a coating to the surface	Claims arising from surface defects or other failure modes directly attributable to the application of paint or other surface lacquering systems, are not covered under warranty		
W	DO NOT use for high impact or high abrasion installations	Claims arising from high impact or high abrasion installations are not protected under warranty		

Technical Data Sheet

Important Information

NOTE		DETAILS
W	DO NOT use decorative face as a cutting surface	Claims arising from physical damage of the decorative surface are not covered under warranty
W	DO NOT expose to heat, hot gases or	Claims arising from frequent or excessive exposure to heat or moisture are not covered under warranty
-	moisture	Claims arising from damage due to front venting oven installations without a heat deflector shield are not covered under warranty
		Claims arising from damage due to fugitive heat or moisture leaking from appliance seals are not covered under warranty
		Claims arising from the use of benchtop hot plates without exhaust fan activation or use of an ineffective extraction, are not covered under warranty
		Claims arising from damage due to hot objects, such as saucepans or irons, contacting the decorative surface, are not covered under warranty
W	ONLY use recommended Care & Maintenance methods	Claims arising from staining or damage attributable to not following Care & Maintenance instructions, are not covered under warranty

W Denotes specific warranty conditions apply